

COMFORT PREMIUM

Viša razina udobnosti, bez kompromisa



PODRUČJE RADA



od -15°C do +50°C



od -25°C do +24°C

ENERGETSKA UČINKOVITOST

A+++ SEER 8,5

A++ SCOP 4,6

Podaci se odnose na model snage 3,5 kW

COMFORT PREMIUM osmišljen je za korisnike koji žele višu razinu udobnosti kroz preciznu kontrolu klime i iznimno tih rad. Inteligentne funkcije automatski prilagođavaju rad uređaja uvjetima u prostoru i pomažu smanjiti potrošnju energije bez oscilacija temperature. Stabilan komfor dodatno podižu senzori i napredne opcije upravljanja.

FUNKCIJE I TEHNOLOGIJE:

- ECO+ – napredna tehnologija za automatsku uštedu energije do 30%
- Intelligent Eye – ušteda energije ovisno o prisutnosti osoba u prostoru
- AI Humidity control – automatsko održavanje optimalne razine vlage u prostoru
- Pouzdano grijanje pri niskim vanjskim temperaturama
- Ionizator + Self-Clean – čišći zrak i jednostavnije održavanje sustava
- Wi-Fi kontrola i upravljanje



	UNUTARNJA	MXI-09HC014i	MXI-12HC014i	MXI-18HC014i	MXI-24HC014i
	VANJSKA	MXO-09HC014i	MXO-12HC014i	MXO-18HC014i	MXO-24HC014i
HLADENJE					
Kapacitet	kW	2.6 (1.0-3.5)	3.5 (1.4-4.0)	5.0 (2.0-6.1)	7.0 (2.2-8.8)
Snaga električnog priključka	W	628	1035	1390	2120
Godišnja potrošnja energije	kWh/a	104	145	206	311
SEER		8.8 (A+++)	8.5(A+++)	8.5(A+++)	7.9(A++)
GRIJANJE					
Kapacitet	kW	2.9 (0.8-3.7)	3.8 (1.1-4.1)	5.4 (1.4-6.8)	7.3 (1.6-9.4)
Snaga električnog priključka	W	666	975	1440	1970
Godišnja potrošnja energije	kWh/a	761	791	1218	1491
SCOP		4.6 (A++)	4.6 (A++)	4.6 (A++)	4.6 (A++)
Max. snaga električnog priključka	W	2200	2200	2800	3800
Max. strujna snaga	A	10	10	13.5	19
UNUTARNJA JEDINICA					
Protok zraka (Hi/Mi/Lo)	m ³ /h	650/510/360/285/150	800/600/450/370/220	950/800/600/470/340	1150/1090/790/635/445
Razina zvučnog tlaka	dB(A)	39/34/25/19.0	39/32/26/20	43/36/28/21.5	46/39.5/32.5/21.5
Neto dimenzije (ŠxDxV)	mm	723x199x286	813x201x289	975x218x308	1055x231x330
Dimenzije sa ambalažom (ŠxDxV)	mm	780x270x365	870x270x365	1035x295x385	1130x405x315
Neto/Gross težina	Kg	7.5/9.6	8/10.4	10.2/13.3	13/16.4
VANJSKA JEDINICA					
Razina zvučnog tlaka	dB(A)	54.0	55	57	60
Neto dimenzije (ŠxDxV)	mm	765x303x555	765x303x555	890x342x673	890x342x673
Dimenzije sa ambalažom (ŠxDxV)	mm	887x337x610	887x337x610	995x398x740	995x398x740
Neto/Gross težina	Kg	23.1/25.4	23.1/25.4	37.8/41	41/44
Rashladno sredstvo	/	R32	R32	R32	R32
Punjenje	Kg	0.55	0.58	0.85	1.08
CJEVOVOD					
Tekućinski vod (tlačni)	mm	6.35	6.35	6.35	6.35
Plinski vod (usisni)	mm	9.52	9.52	12.7	12.7
Max. dozv.dulj.cjevo.bez.nadopune	m	5	5	5	5
Nadopuna po dodatnom metru	g/m	12	12	12	12
Max. dozvoljena duljina cjevovoda	m	25	25	30	50
Max. visinska razlika	m	10	10	20	25
Temperaturni raspon rada - hlađenje	°C	-15--+50	-15--+50	-15--+50	-15--+50
Temperaturni raspon rada - grijanje	°C	-25--+24	-25--+24	-25--+24	-25--+24
Razmak nogica	mm	452	452	663	663
Međuveza	mm ²	1.5x5	1.5x5	1.5x5	2.5x5
Gdje je napajanje (Unutarnje / Vanjsko)	mm ²	VJ	VJ	VJ	VJ



SUPER GRIJANJE



ECO+



INTELLIGENT EYE



AI HUMIDITY CONTROL



WI-FI



56°C STERILIZACIJA



IONIZATOR



AUTO SWING



I FEEL



I-REMOTE



NOĆNI RAD



TURBO NAČIN RADA



ODVLAŽIVANJE



AUTO RESTART



24H TIMER