

COMFORT PREMIUM

Enhanced comfort, without compromise



OPERATING RANGE



-15°C to +50°C



-25°C to +24°C

ENERGY EFFICIENCY

A+++ SEER 8.5

A++ SCOP 4.6

Data refers to the 3.5 kW model.


COMFORT PREMIUM is designed for users seeking precise climate control and exceptionally quiet operation. Intelligent features automatically adjust operation to room conditions, helping reduce energy consumption while maintaining a stable temperature. Sensors and advanced control options further improve the overall indoor climate.

FEATURES & TECHNOLOGIES:

- ECO+ – advanced technology for automatic energy savings of up to 30%
- Intelligent Eye – energy-saving operation based on room occupancy
- AI Humidity Control – automatic control of optimal indoor humidity levels
- Reliable heating at low outdoor temperatures
- Even air distribution (3D Airflow)
- Wi-Fi control via mobile app



	INDOOR	MXI-09HC014i	MXI-12HC014i	MXI-18HC014i	MXI-24HC014i
	OUTDOOR	MXO-09HC014i	MXO-12HC014i	MXO-18HC014i	MXO-24HC014i
COOLING					
Capacity	kW	2.6 (1.0-3.5)	3.5 (1.4-4.0)	5.0 (2.0-6.1)	7.0 (2.2-8.8)
Power input	W	628	1035	1390	2120
Annual energy consumption	kWh/a	104	145	206	311
SEER		8.8 (A+++)	8.5 (A+++)	8.5 (A+++)	7.9 (A++)
HEATING					
Capacity	kW	2.9 (0.8-3.7)	3.8 (1.1-4.1)	5.4 (1.4-6.8)	7.3 (1.6-9.4)
Power input	W	666	975	1440	1970
Annual energy consumption	kWh/a	761	791	1218	1491
SCOP		4.6 (A++)	4.6 (A++)	4.6 (A++)	4.6 (A++)
Max. power input	W	2200	2200	2800	3800
Max. operating current	A	10	10	13.5	19
INDOOR UNIT					
Airflow (Hi/Mi/Lo)	m³/h	650/510/360/285/150	800/600/450/370/220	950/800/600/470/340	1150/1090/790/635/445
Sound pressure level (Hi/Mi/Lo)	dB(A)	39/34/25/19.0	39/32/26/20	43/36/28/21.5	46/39.5/32.5/21.5
Net dimensions (W×D×H)	mm	723x199x286	813x201x289	975x218x308	1055x231x330
Package dimensions (W×D×H)	mm	780x270x365	870x270x365	1035x295x385	1130x405x315
Net/Gross weight	Kg	7.5/9.6	8/10.4	10.2/13.3	13/16.4
OUTDOOR UNIT					
Sound power level	dB(A)	54.0	55	57	60
Net dimensions (W×D×H)	mm	765x303x555	765x303x555	890x342x673	890x342x673
Packed dimensions (W×D×H)	mm	887x337x610	887x337x610	995x398x740	995x398x740
Net/Gross weight	Kg	23.1/25.4	23.1/25.4	37.8/41	41/44
Refrigerant type	/	R32	R32	R32	R32
Refrigerant charge	Kg	0.55	0.58	0.85	1.08
PIPING					
Liquid pipe diameter	mm	6.35	6.35	6.35	6.35
Gas pipe diameter	mm	9.52	9.52	12.7	12.7
Pre-charged pipe length	m	5	5	5	5
Additional refrigerant charge per metre	g/m	12	12	12	12
Max. pipe length	m	25	25	30	50
Max. height difference	m	10	10	20	25
Operating range – cooling	°C	-15~+50	-15~+50	-15~+50	-15~+50
Operating range – heating	°C	-25~+24	-25~+24	-25~+24	-25~+24
Mounting dimensions	mm	452	452	663	663
Interconnecting cable	mm²	1.5x5	1.5x5	1.5x5	2.5x5
Power supply location (Indoor / Outdoor)	mm²	OU	OU	OU	OU


SUPER HEATING

ECO+

INTELLIGENT EYE


AI HUMIDITY CONTROL

3D AIRFLOW

WI-FI

56°C STERILISATION

AUTO SWING

I FEEL

I-REMOTE

NIGHT MODE

TURBO MODE

DEHUMIDIFICATION

AUTO RESTART

24H TIMER