



MAXON FRESH R32



PODRUČJE RADA



OD -15°C
DO +50°C



OD -15°C
DO +30°C

ENERGETSKA UČINKOVITOST



SEER
6,1



SCOP
4

Podaci se odnose na model snage 3,5 kW

		VANJSKA UNUTARNJA	MXI-09HC011i MXO-09HC011i	MXI-12HC011i MXO-12HC011i	MXI-18HC011i MXO-18HC011i	MXI-24HC011i MXO-24HC011i
HLADENJE	Kapacitet	kW	2,6 (0,9 - 3,4)	3,5 (1,1 - 4,1)	5,2 (1,8 - 6,1)	7,0 (2,0 - 7,9)
	Snaga električnog priključka	W	710	1237	1539	2345
	Potrošnja struje	A	3,1	5,4	6,9	10,2
	SEER		6,2 (A++)	6,1 (A++)	7,1 (A++)	6,1 (A++)
GRIJANJE	Kapacitet	kW	2,9 (0,8 - 3,37)	3,8 (1 - 4,2)	5,6 (1,3 - 6,7)	7,3 (1,6 - 8,8)
	Snaga električnog priključka	W	739	964	1480	2035
	Potrošnja struje	A	3,2	4,2	6,4	10,2
	SCOP		4,0 (A+)	4 (A+)	4 (A+)	4 (A+)
	Max. snaga električnog priključka	W	2150	2150	2950	3850
	Max. strujna snaga	A	10	10	13,5	17,5
UNUTARNJA JEDINICA	Protok zraka (Hi/Mi/Lo)	m ³ /h	520/460/360	600/500/360	840/680/540	980/817/662
	Odvlaživanje	(L/h)	1	1,2	1,8	2,4
	Razina buke (Hi/Mi/Lo)	dB(A)	40/30/26/21	40/34/26/22	44/37/30/25	44,5/42/34,5/28
	Neto dimenzije (ŠxDxV)	mm	805x194x285	805x194x285	957x213x302	1040x220x327
	Dimenzije sa ambalažom (ŠxDxV)	mm	870x270x360	870x270x360	1035x295x380	1120x405x310
	Neto/Gross težina	Kg	7.5/9.7	7.5/9.7	10/13	12.3/15.8
VANJSKA JEDINICA	Razina buke	dB(A)	55.5	56	56	59.5
	Neto dimenzije (ŠxDxV)	mm	700x275x550	700x275x550	800x333x554	845x363x702
	Dimenzije sa ambalažom (W*H*D)	Kg	815x325x615	815x325x615	920x390x615	965x395x765
	Neto/Gross težina	Kg	22.7/25.2	22.7/25.2	34/36.7	51.5/54.5
	Rashladno sredstvo	/	R32	R32	R32	R32
	Punjenje	Kg	0.5	0.5	1.00	1.6
CJEVOVOD	Tekućinski vod (tlačni)	mm	6.35	6.35	6.35	6
	Plinski vod (usisni)	mm	9,52	9,52	12,7	15,9
	Max. dozv.dulj.cjevo. bez nadopune	m	5	5	5	Ø 10
	Nadopuna po dodatnom metru	g/m	15 g	15 g	15 g	30 g
	Max. dozvoljena duljina cjevovoda	m	25	25	30	50
	Max. visinska razlika	m	10	10	20	25
Područje rada (hlađenje/grijanje) - unutarnja	°C	17-32/0-30	17-32/0-30	17-32/0-30	17-32/0-30	
Područje rada (hlađenje/grijanje) - vanjska jedinica	°C	-15-50/-15-30	-15-50/-15-30	-15-50/-15-30	-15-50/-15-30	
Razmak nogica na vanjskoj jedinici	mm	460	460	514	540	
Međuveza	mm ²	5 x 1,5	5 x 1,5	5 x 1,5	5 x 1,5	
Gdje je napajanje (Unutarnje / Vanjska)	mm ²	V 3 x 1,5	V 3 x 1,5	V 3 x 2,5	V 3 x 2,5	