

KOMPAKTNI KAZETNI MODEL

maxon



MODEL		UNUTARNJA	MXI-12HCA013I	MXI-18HCA013I
		VANJSKA	MXO-1U12HCO013I	MXO-1U18HCO013I
HLADENJE	Kapacitet	kW	3,5 (0,85 - 4,11)	5,3 (2,90 - 5,59)
	Snaga električnog priključka	W	1010	1633
	Potrošnja struje	A	4,4	7,2
	SEER		6,6 (A++)	6,3 (A++)
GRIJANJE	Kapacitet (W)	kW	3,8 (0,47 - 4,31)	5,5 (2,37 - 6,10)
	Snaga električnog priključka (W)	W	1019	1540
	Potrošnja struje (A)	A	4,7	6,8
	SCOP		4,1 (A+)	4,0 (A+)
	Max, snaga električnog priključka	W	1850	2950
	Max, strujna snaga	A	9	13,5
UNUTARNJA JEDINICA	Protok zraka (Hi/Mi/Lo)	m³/h	620/510/420	720/620/500
	Razina buke (Hi/Mi/Lo)	dB(A)	41/36/33/25.5	43/39.5/35.5/29
	Neto dimenzije (ŠxDxV)	mm	570x570x260	570x570x260
	Dimenzije sa ambalažom (ŠxDxV)	mm	655x655x290	662x662x317
	Neto/Gross težina	Kg	16.3/20.4	16/20.6
Panel MX-PTMB-03	Panel Neto dimenzije (ŠxDxV)	mm	647x647x50	647x647x50
	Panel Dimenzije sa ambalažom (ŠxDxV)	mm	715x715x123	715x715x123
	Panel Neto/Gross težina	Kg	2.5/4.5	2.5/4.5
VANJSKA JEDINICA	Razina buke	dB(A)	60	63
	Neto dimenzije (ŠxDxV)	mm	765x303x555	805x330x554
	Dimenzije sa ambalažom (ŠxDxV)	mm	887x337x610	915x370x615
	Neto/Gross težina	kg	26,6/29	32,5/35,2
	Rashladno sredstvo		R32	R32
Punjenje	kg	0,72	1,15	
CJEVOVOD	Tekućinski vod (tlačni)	mm	6.35	6.35
	Plinski vod (usisni)	mm	9,52	12,7
	Max. dozv.dulj.cjevo. bez nadopune	m	5	5
	Nadopuna po dodatnom metru	g/m	12	12
	Max. dozvoljena duljina cjevovoda	m	25	30
	Max. visinska razlika	m	10	20
Područje rada (hlađenje/grijanje)	°C	-16 ~ +30	-16 ~ +30	
Razmak nogica na vanjskoj jedinici	mm	452	511	
Napajanje vanjske jedinice	mm²	3x1,5	3x1,5	
Napajanje unutarnje jedinice		220-240V,1Ph 50Hz	220-240V,1Ph 50Hz	
Veza	mm²	4x1,5	4x1,5	

PREDNOSTI:

- 360 ispuh zraka • LED display • Pumpa odvoda kondenzata
- Individualna kontrola klapani • Mogućnost centralne kontrole
- Grijач kadice kondenzata • Grijач kompresora



360° ISPUH ZRAKA



LED DISPLAY



PUMPA ODVOVA KONDENZATA



INDIVIDUALNA KONTROLA KLAPANI



MOGUĆNOST CENTRALNE KONTROLE



GRIJAČ KADICE KONDENZATA



GRIJAČ KOMPRESORA