



MODEL		UNUTARNJA	MXI-24HCA013i	MXI-36HCA013i	MXI-48HCA013i	MXI-55HCA013i
		VANJSKA	MXO-1U24HCO013i	MXO-1U36HCO013i	MXO-1U48HCO013i	MXO-1U55HCO013i
HLADENJE	Kapacitet	kW	7,0 (3,30 - 7,91)	10,55 (2,70 - 11,43)	14,07 (3,52 - 15,83)	15,24 (4,10 - 16,71)
	Snaga električnog priključka	W	2320	3950	4650	5000
	Potrošnja struje	A	10,2	17,5	8,1	60
	SEER		6,2 (A++)	6,7 (A++)	6,1 (A++)	6,3 (A++)
GRIJANJE	Kapacitet (W)	kW	7,62 (2,81 - 8,94)	11,14 (2,78 - 12,30)	16,12 (4,10 - 17,29)	18,17 (4,40 - 19,93)
	Snaga električnog priključka (W)	W	1900	3000	4580	5550
	Potrošnja struje (A)	A	8,5	11,0	8,0	9,6
	SCOP		4,0 (A+)	4,0 (A+)	4,0 (A+)	4,0 (A+)
	Max, snaga električnog priključka	W	3700	5000	6900	7500
Max, strujna snaga	A	19	22,5	13	14	
UNUTARNJA JEDINICA	Protok zraka (Hi/Mi/Lo)	m³/h	1300/1140/1000	1700/1550/1380	1970/1780/1580	2000/1850/1650
	Razina buke (Hi/Mi/Lo)	dB(A)	45.5/42.5/39.5/27	50/47.5/44.5/39	51/48.5/46.5/37.5	53/50.5/48/40
	Neto dimenzije (ŠxDxV)	mm	830x830x205	830x830x245	830x830x287	830x830x287
	Dimenzije sa ambalažom (ŠxDxV)	mm	910x910x250	910x910x290	910x910x330	910x910x330
	Neto/Gross težina	Kg	21.6/25.4	27.2/31.2	29.3/33.5	29.3/33.5
MX PTMB04	Panel Neto dimenzije (ŠxDxV)	mm	950x950x55	950x950x55	950x950x55	950x950x55
	Panel Dimenzije sa ambalažom (ŠxDxV)	mm	1035x1035x90	1035x1035x90	1035x1035x90	1035x1035x90
	Panel Neto/Gross težina	Kg	6/9	6/9	6/9	6/9
VANJSKA JEDINICA	Razina buke	dB(A)	67	70	73	73
	Neto dimenzije (ŠxDxV)	mm	890x342x673	946x410x810	952x415x1333	952x415x1333
	Dimenzije sa ambalažom (ŠxDxV)	mm	995x398x740	1090x500x885	1095x495x1480	1095x495x1480
	Neto/Gross težina	kg	43.9/46.9	66.9/71.5	103.7/118.3	107.0/121.2
	Rashladno sredstvo		R32	R32	R32	R32
Punjenje	kg	1,5	2,4	2,9	3,0	
CJEVOD	Tekućinski vod (tlačni)	mm	9,52	9,52	9,52	9,52
	Plinski vod (lusisni)	mm	15,9	15,9	15,9	15,9
	Max. dozvolj. cjevo. bez nadopune	m	5	5	5	5
	Nadopuna po dodatnom metru	g/m	24	24	24	24
	Max. dozvoljena duljina cjevovoda	m	50	75	75	75
	Max. visinska razlika	m	25	30	30	30
	Područje rada (hlađenje/grijanje)	°C	-16 ~ +30	-16 ~ +30	-16 ~ +30	-16 ~ +30
Razmak nogica na vanjskoj jedinici	mm	663	673	634	634	
Napajanje vanjske jedinice	mm²	3x2,5	5x2,5	5x2,5	5x2,5	
Napajanje unutarnje jedinice		220 240V, 1Ph 50Hz	220 240V, 1Ph 50Hz	380 415V, 3 Ph, 50Hz	380 415V, 3 Ph, 50Hz	
Veza	mm²	4x1,5	4x1,5	4x1,5	4x1,5	
Žičani daljinski - opcija						

PREDNOSTI:

- 360 ispuh zraka • LED display • Pumpa odvoda kondenzata
- Individualna kontrola klapni • Mogućnost centralne kontrole • Twins system

