

	INDOOR	MXI-12HC01i	MXI-18HC01i	
	OUTDOOR	MXO-12HC01i	MXO-18HC01i	
COOLING	Capacity	kW	3,5 (1,38 - 4,31)	5,3 (3,39 - 5,90)
	Power input	W	1096	1550
	Annual electricity consumption	kWh/a	182	265
	SEER		7 (A++)	7 (A++)
HEATING	Capacity	kW	3,8 (1,07 - 4,46)	5,6 (3,10 - 5,9)
	Power input	W	1027	1630
	Annual electricity consumption	kWh/a	833	1470
	SCOP		4,2 (A+)	4,0 (A+)
	Max. power input	W	2150	2500
	Max. Operating Current	A	10	13
INDOOR UNIT	Air flow (Hi/Mi/Lo)	m ³ /h	530/400/350	800/600/500
	Moisture removal	(L/h)	1,2	2,2
	Sound pressure level (Hi/Mi/Lo)	dB(A)	37/32/22/21	41/37/31/20
	Net dimensions (WxLxH)	mm	835x208x295	969x241x320
	Dimensions with packaging (WxLxH)	mm	905x355x290	1045x315x405
	Net/Shipping Weight	Kg	8,7/11,5	11,2/14,6
OUTDOOR UNIT	Sound power level	dB(A)	56	57
	Net dimensions (WxLxH)	mm	720x270x495	805x330x554
	Dimensions with packaging (WxLxH)	mm	835x300x540	915x370x615
	Net/Shipping Weight	Kg	23,7/25,5	33,5/36,1
	Refrigerant type	/	R32	R32
	Refrigerant charge	Kg	0,65	1,1
PIPELINE	Liquid Side Diameter	mm	6,35	6,35
	Gas Side Diameter	mm	9,52	12,7
	Max. pipe length (Pre-charge)	m	5	5
	Additional charge per metre	g/m	12	12
	Max. refrigerant pipe length	m	25	30
	Max. difference in level	m	10	20
Operating range- cooling	°C	-15--+50	-15--+50	
Operating range - heating	°C	-20--+24	-20--+24	
Mounting holes spacing - outdoor	mm	452	511	
Interconnect cable	mm ²	5 x 1,5	5 x 1,5	
Power Supply IU / OU	mm ²	OU 3 x 1,5	OU 3 x 1,5	

