

	INDOOR	MXI-09HC012i	MXI-12HC012i	MXI-18HC012i	MXI-24HC012i	
	OUTDOOR	MXO-09HC012i	MXO-12HC012i	MXO-18HC012i	MXO-24HC012i	
COOLING	Capacity	kW	2,6 (1,0 - 3,2)	3,5 (1,4 - 4,3)	5,3 (3,4 - 6,0)	7,0 (2,1 - 8,2)
	Power input	W	613	977	1550	2340
	Annual electricity consumption	kWh/a	98	146	265	377
	SEER		9,3 (A+++)	8,5 (A+++)	7 (A++)	6,5 (A++)
HEATING	Capacity	kW	2,9 (0,8 - 3,4)	3,8 (1,1 - 4,4)	5,6 (3,1 - 6,0)	7,3 (1,5 - 8,2)
	Power input	W	637	977	1500	2130
	Annual electricity consumption	kWh/a	743	791	1435	1730
	SCOP		4,6 (A++)	4,6 (A++)	4,0 (A+)	4,0 (A+)
Max. power input	W	2200	2200	2500	3700	
Max. Operating Current	A	10,5	10,5	13	19	
INDOOR UNIT	Air flow (Hi/Mi/Lo)	m ³ /h	483/362/303	584/477/395	730/500/420	1020/830/640
	Moisture removal	(L/h)	0,80	1,2	2,2	3
	Sound pressure level (Hi/Mi/Lo)	dB(A)	37/29/24/20	40/33/25/21	43/34/28/23	47/42/31/25
	Net dimensions (WxLxH)	mm	802x189x297	802x189x297	965x215x319	1080x226x335
	Dimensions with packaging (WxLxH)	mm	875x285x380	875x285x380	1045x305x410	1155x415x320
	Net/Shipping Weight	Kg	8,6/11,1	8,6/11,1	10,9/14,2	13,7/17,3
OUTDOOR UNIT	Sound power level	dB(A)	54	55	56	61
	Net dimensions (WxLxH)	mm	765x303x555	765x303x555	805x330x554	890x342x673
	Dimensions with packaging (WxLxH)	mm	887x337x610	887x337x610	915x370x615	995x398x740
	Net/Shipping Weight	Kg	26,4/28,8	26,4/28,7	33,5/36,1	43,9/46,9
	Refrigerant type	/	R32	R32	R32	R32
	Refrigerant charge	Kg	0,62	0,62	1,1	1,45
PIPELINE	Liquid Side Diameter	mm	6,35	6,35	6,35	9,52
	Gas Side Diameter	mm	9,52	9,52	12,7	15,9
	Max. pipe length (Pre-charge)	m	5	5	5	5
	Additional charge per metre	g/m	12	12	12	24
	Max. refrigerant pipe length	m	25	25	30	50
	Max. difference in level	m	10	10	20	25
Operating range- cooling	°C	-15--+50	-15--+50	-15--+50	-15--+50	
Operating range - heating	°C	-20--+24	-20--+24	-20--+24	-20--+24	
Mounting holes spacing - outdoor	mm	452	452	511	663	
Interconnect cable	mm ²	5 x 1,5	5 x 1,5	5 x 1,5	5 x 2,5	
Power Supply IU / OU	mm ²	OU 3x1,5	OU 3x1,5	OU 3x2,5	OU 3x2,5	



ECO REFRIGERANT



WI-FI



NIGHT MODE



DEHUMIDIFICATION




IONISER



ECO MODE



REFRIGERANT LACK DETECTION



HD FILTER



LOUVER POSITION MEMORY



SELF-CLEAN



SUPER HEATING



FOLLOW ME



BLUE FIN



AUTO RESTART



24H TIMER



ERROR DETECTION