

	INDOOR	MXI-09HE013i	MXI-12HE013i	MXI-18HE013i	
	OUTDOOR	MXO-09HE013i	MXO-12HE013i	MXO-18HE013i	
COOLING	Capacity	kW	2,5(0,8-3,0)	3,2(0,8-3,5)	4,6(1,3-5,3)
	Power input	W	830	1140	1500
	Annual electricity consumption	kWh/a	143	184	256
	SEER		6,1(A++)	6,1(A++)	6,3(A++)
HEATING	Capacity	kW	2,8(0,8-3,3)	3,4(0,8-3,6)	4,6(1,3-5,3)
	Power input	W	870	1210	1350
	Annual electricity consumption	kWh/a	735	910	1155
	SCOP		4,0 (A+)	4,0 (A+)	4,0 (A+)
	Max. power input	W	1200	1500	1750
	Max. Operating Current	A	7,1	7,1	7,5
INDOOR UNIT	Air flow (Hi/Mi/Lo)	m ³ /h	490	510	700
	Moisture removal	(L/h)	1,0	1,4	2
	Sound pressure level (Hi/Mi/Lo)	dB(A)	38/34/30/24	39/35/31/24	44/40/35/28
	Net dimensions (WxLxH)	mm	708/190/263	708/190/263	865/200/290
	Dimensions with packaging (WxLxH)	mm	772/325/263	772/325/263	928/353/273
	Net/Shipping Weight	Kg	7,4/8,8	7,8/9,2	8,7/10,9
OUTDOOR UNIT	Sound power level	dB(A)	50	50	54
	Net dimensions (WxLxH)	mm	700/245/544	700/245/544	800/280/553
	Dimensions with packaging (WxLxH)	mm	819/320/592	819/320/592	902/375/607
	Net/Shipping Weight	Kg	21,8/23,9	22,9/25,0	29,2/32,1
	Refrigerant type	/	R32	R32	R32
	Refrigerant charge	Kg	0,5	0,55	0,68
PIPELINE	Liquid Side Diameter	mm	6,35	6,35	6,35
	Gas Side Diameter	mm	9,52	9,52	12,7
	Max. pipe length (Pre-charge)	m	5	5	7
	Additional charge per metre	g/m	20	20	20
	Max. refrigerant pipe length	m	20	20	20
	Max. difference in level	m	10	10	15
Operating range - cooling	°C	-10-43	-10-43	-10-43	
Operating range - heating	°C	-15-24	-15-24	-15-24	
Mounting holes spacing - outdoor	mm	440	440	510	
Interconnect cable	mm ²	4x1,5	4x1,5	4x1,5	
Power Supply IU / OU	mm ²	IU	IU	OU	

