

		UNUTARNJA	MXI-12HB013i	MXI-18HB013i
		VANJSKA	MXO-12HB013i	MXO-18HB013i
HLADENJE	Kapacitet	kW	3,6 (0,80 - 4,0)	5,3 (2,0 - 6,3)
	Snaga električnog priključka	W	1114	1510
	Godišnja potrošnja energije	kWh/a	136	218
	SEER		8,5 (A+++)	8,5 (A+++)
GRIJANJE	Kapacitet	kW	3,9 (0,8 - 4,5)	5,8 (1,35 - 6,8)
	Snaga električnog priključka	W	1051	1450
	Godišnja potrošnja energije	kWh/a	852	1400
	SCOP		4,6 (A++)	4,6 (A++)
	Max. snaga električnog priključka	W	1530	2700
	Max. strujna snaga	A	6,95	12,3
UNUTARNJA JEDINICA	Protok zraka (Hi/Mi/Lo)	m ³ /h	670/670	930/980
	Odvlaživanje	(L/h)	1,4	2,3
	Razina buke (Hi/Mi/Lo)	dB(A)	38/33/29/18	44/40/36/31
	Neto dimenzije (ŠxDxV)	mm	805x200x292	975x220x318
	Dimenzije sa ambalažom (ŠxDxV)	mm	876x272x365	1050x301x397
	Neto/Gross težina	Kg	8,6/10,8	11,6/14,4
VANJSKA JEDINICA	Razina zvučnog tlaka	dB(A)	51	55
	Neto dimenzije (ŠxDxV)	mm	800x280x553	820x306x642
	Dimenzije sa ambalažom (ŠxDxV)	mm	902x375x614	940x390x697
	Neto/Gross težina	Kg	28,5/31,4	37,8/40,5
	Rashladno sredstvo	/	R32	R32
	Punjenje	Kg	0,65	1,1
CJEVOD	Tekućinski vod (tlačni)	mm	6,35	6,35
	Plinski vod (usisni)	mm	9,52	12,7
	Max. dozv.dulj.cjevo.bez.nadopune	m	7	7
	Nadopuna po dodatnom metru	g/m	20	20
	Max. dozvoljena duljina cjevovoda	m	20	25
	Max. visinska razlika	m	10	15
Temperaturni raspon rada - hlađenje	°C	-20--+43	-20--+43	
Temperaturni raspon rada - grijanje	°C	-25--+24	-25--+24	
Razmak nogica	mm	440	490	
Međuveza	mm ²	4 x 1,5	4 x 1,5	
Gdje je napajanje (Unutarnje / Vanjsko)	mm ²	V 3 x 1,5	V 3 x 1,5	



EKOSMART
GRIJANJE



-25°C
GRIJANJE



3D ISPUH
ZRAKA



COANDA
PROTOK ZRAKA



3-MINUTNA
ZAŠTITA



SUPER
GRIJANJE



FOLLOW
ME



WI-FI



SUPER TIHI
RAD 20 DB(A)



56°C
STERILIZACIJA



IONIZATOR



FROST CLEAN



ECO RADNA
TVAR



TURBO
NAČIN RADA



ECO
NAČIN RADA



NOĆNI RAD



ODVLAŽIVANJE



MEMORIJA
POLOŽAJA
KLAPNE



REGULACIJA
BRZINE
VENTILATORA



BLUE FIN



24h
TIMER



AUTO RESTART